





PP 熔喷与不同材质骨架和保护层覆合,以满足特定性能要求: PP meltblown combined with different carriers and protection layers to meet specific performance requirements: 滤效等级 | Efficiency: F5-H14 (45% - 99.995%) 阻力 | Pressure Drop: 5-38 Pa

应用市场: 净化器、吸尘器、民用/医用口罩、汽车空调、暖通空调、净化室等
Applications: Air purifier, Vacuum cleaner, Residential/Medical face mask, Automotive cabin air, Air conditioner, Clean room, and etc.

## 产品优势 | Advantages: 产品组合丰富,可根据客户要求定制。

Rich product portfolio and flexible customize capability. 阻力低于同类竞品,质量稳定,使用寿命长。 Lower pressure drop, consistent quality and strong durability.

Туре	Area Weight (g/m²)	Thickness (mm)	Initial Efficiency* (%)	Pressure Drop* (Pa)	Max. Width (mm)	Roll Length (m)
MR-P65%	80 ± 10	$0.55 \pm 0.05$	≥85	5 - 6	1470	500
MR-P85%	80 ± 10	$0.55 \pm 0.05$	≥85	8 - 10		
MR-P90%	80 ± 10	$0.55 \pm 0.05$	≥90	9 - 11		
MR-P95%	80 ± 10	$0.55 \pm 0.05$	≥95	12 - 14		
MR-P98%	80 ± 10	$0.55 \pm 0.05$	≥98	13 – 15		
MR-P99.5%	80 ± 10	$0.55 \pm 0.05$	≥99.5	18 – 20		
MR-P99.97%	90 ± 10	$0.65 \pm 0.05$	≥99.97	26 – 29		
MR-P99.99%	95 ± 10	0.75 ± 0.05	≥99.995	34 - 37		

## 产品技术参数 | Product Technical Data

\* 测试条件 | Testing condition: 0.3µm NaCl @ 5.3cm/s

无纺布基材可按客户要求定制。| Carrier material can be customized according to requirement from customers.

## 免责声明/Disclaimer

该资料中产品的公开性能参数不属于对产品质量具有法律约束力的声明。 这些性能参数不会成为合同的组成部分。它们代表在制造时根据适用的测试方法获得的平均值, 并受正常生产波动的影响。 产品参数如有更改,恕不另行通知。 如需了解更多产品信息,请联系名冠。

The disclosed performances and measured values of the product in this document are not legally binding statements of product quality. These performances and values will not form part of the contract. They represent average values obtained at the time of manufacture according to applicable test methods and are subject to normal manufacturing variations. The products properties are subject to change without prior notice. Please contact Mingguan for more information.